



BE LGN25 HF C Z1U 5G4 Std R0,5

Prf SAFE 25mm+H07Z1-U Cca (a1d1s1) 5G4 G/Y BL BR BLA GR C50

Properties of the article

◦ Articlenumber	1234000636
◦ Barcode	5420056264044
◦ Category	Energy & Light
◦ Gross weight (kg)	15.7
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	50

Properties of the Preflex[®] tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Light Green
◦ Outer diameter (mm)	25
◦ Inner diameter (mm)	18.3
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

◦ Cable type	H07Z1-U 5G4
◦ Color	
◦ Insulation	LS0H
◦ CPR Class	cca s1 d1 a1

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	EN 50565-1 ; EN 50565-2

Certificates

