



BE LGN20 HF C 2xUTP6 R1

Preflex SAFE 20mm+2xU/UTP LS0H Cca (a1d2s1) CAT6 C100

Properties of the article

◦ Articlenumber	1234001248
◦ Barcode	5420056257299
◦ Category	Data
◦ Gross weight (kg)	14.2
◦ Dimensions (WxLxH)	500 x 500 x 200 MM
◦ Packaging	Roll
◦ Length	100

Properties of the Preflex® tube

◦ Material of tube	Halogen-free Polypropylene
◦ Color	Light Green
◦ Outer diameter (mm)	20
◦ Inner diameter (mm)	14.1
◦ Classification	ICTA 3422
◦ Pressure resistance	750N / 23°C
◦ Impact resistance	6J / -5°C
◦ Breakthrough test	2000V / 50-60 Hz 15min.
◦ Insulation resistance	min. 100 Mohm/80cm
◦ Test temperature	-5°C tot +90°C
◦ Min. installation temperature	-5°C

Characteristics of the cable or cable combination

	U/UTP LS0H CAT6	U/UTP LS0H CAT6
◦ Cable type		
◦ Color		
◦ Insulation	LS0H	
◦ CPR Class	cca s1 d1 a1	

Certificates

◦ Norm van de buis	EN 61386-1, EN 61386-22, EN 60423; EN 61034, EN 60754-1, EN 60754-2
◦ Norm van de kabel	ISO/IEC 11801 :2011 (Ed. 2.2) ; IEC 61156-5:2012 (Ed. 2.1) ; EN 50173-1 :2011 ; EN 50173-2:2007 including amendment A 1:2010 ; EN 50288-6-1 :2013 ; ANSI/TIA-568-C.2:2009

Certificates

